

# NLG Super Bungee Tool Lanyard

Product Code:  
101419

Max Load:  
20 KG / 44 LBS



## OVERVIEW

The Super Bungee Tool Lanyard comfortably stretches to over 3 metres allowing for the safe use of heavy tools when working on a platform. Featuring a low-resistance Super Bungee allowing for ease of use and high-strength webbing it truly is designed with functionality and safety in mind.

## VIEW ONLINE

<https://neverletgo.com/products/super-bungee-tool-lanyard/>



## NLG ID™ Serialised and safe

Simply scan the NLG ID tag with your phone to instantly access certificates, instruction videos and log inspections. (See Specification if included).



## Third-party tested and certified

Independent laboratory load testing certificates and Declarations of Conformity are available on request. Please contact [team@neverletgo.com](mailto:team@neverletgo.com).

DESCRIPTION	<p>With The Super Bungee Tool Lanyard stretching to over 3 metres, no one will ever be able to complain about not having enough reach! It has been developed for users of MEWPs or working platforms who are using the attachment point in the platform cage or cradle itself.</p> <p>The Lanyard has been designed with the user in mind, the low resistance bungee provides all-day comfort whilst the large gated double action carabiner allows for easy connection and disconnection even whilst wearing gloves. The large webbing loop at the opposite end of the lanyard provides the widest number of options for attachment to tools of varied sizes or easy attachment to a fixed anchor point.</p> <p>Note: For fixed anchor point use only. This tool lanyard is not designed to be attached directly to the user.</p>	
FEATURES	<p>Low recoil force and extra long reach make it ideal for elevated platform use</p> <p>Compact design reduces snagging hazards</p> <p>Double-action automatic locking carabiner for extra security and ease of use</p> <p>Extra high-strength webbing delivers ultimate peace of mind</p> <p>Heavy-duty wear protector sleeve provides an additional layer of structural protection</p> <p>Faster visual inspections with heavy-duty contrast stitching</p> <p>Clever contrast wear indicators ensure early warning of any structural damage</p>	
TECHNICAL SPECIFICATION	<p>Max Load: 20 KG / 44 LBS</p> <p>Safety Standards: ANSI/ISEA 121-2018, CE / UKCA</p> <p>Load Tested and Third-party Certified: Dynamic (2:1 Safety Factor)</p> <p>NLG ID™ Technology / Scannable Compatible</p> <p>Unique Serial Number</p> <p>Dimensions: Extends from 160cm to 340cm</p>	
RETAIL	EAN (GTIN-13) 5060572180307	UNIT WEIGHT (G) 345
SHIPPING	HS CODE 5609.00.0000	COUNTRY OF ORIGIN Taiwan



## Super Bungee Tool Lanyard

Product Code: 101419

---

View online

<https://neverletgo.com/products/super-bungee-tool-lanyard/>

Learn more about:

[Dropped object prevention](#)

[Tool tethering](#)

[Tool lanyards](#)

Useful resources:

[Tool Box](#)

[Tool Tether Guide](#)

[Library](#)

---

### CONTACT

[+44 \(0\)330 016 0030](tel:+443300160030)

[neverletgo.com](https://neverletgo.com)

---

### INSPECTION

In addition to routine checks before each use, all equipment should undergo regular detailed inspections, conducted and recorded by a competent person using the NLG Inspection Checklist. If any part is worn or shows signs of degradation, immediately retire from service. In the event of a drop, quarantine the equipment for a thorough inspection.

[Click to download Inspection Checklist](#)

---

### LEGAL

NLG makes every effort to ensure the information in this Datasheet is accurate and current. However, NLG reserves the right to change the product specification when necessary. NLG cannot be held responsible for any inaccuracies or omissions.

Copyright © 2023. NLG® and Never Let Go® are registered trademarks.

---